

CENTRIFUGAL SPRAYER PUMPS



9303 SERIES
 • 1 1/2" Inlet
 • 1 1/4" Outlet

9304-9305 &
 9306 SERIES
 • 2" Inlet
 • 1 1/2" Outlet

9307 SERIES
 • 3" Inlet
 • 2" Outlet



PART	MAX GPM	MAX PSI	HYD GPM	HYPRO HYDRAULIC PUMPS DESCRIPTION	lbs ea.	PRICE
9303C-HM1C	114	130	13	Cast iron Pump for open/close center	26	\$749
9303C-HM2C	97	95	6	Cast iron Pump for closed center	26	749
9303C-HM4C	115	93	7	Cast iron Pump for open/closed center	26	749
9303C-HM5C	147	145	16	Cast iron Pump for open/closed center	26	749
9306C-HM1C	207	130	13	Cast iron Pump for open/closed center	33	879
9306C-HM5C	212	140	17	Cast iron Pump for open/closed center	33	879
9307C-GM10	358	135	20	CI Pump for o/c center, hyd gear motor, SC seal	86	2999
3430-0332				Seal and O-ring repair kit ceramic	3oz	44
3430-0589				Life Guard™ silicon carbide seal and o-ring	3oz	164
3430-0500				Seal and o-ring repair kit for Model 9305C-HM3C	3oz	46
2120-0009				Seal only	3oz	39
9303S-HM1C	114	130	13	316 Stainless Steel Pump for open/closed center	26	1282
9303S-HM2C	97	95	6	316 Stainless Steel Pump for open/closed center	26	1282
9303S-HM4C	115	93	7	316 Stainless Steel Pump for open/closed center	26	1399
9303S-HM5C	147	145	16	316 Stainless Steel Pump for open/closed center	26	1399
9306S-HM1C	207	130	13	316 Stainless Steel Pump for open/closed center	33	1516
9306S-HM5C	212	140	17	316 Stainless Steel Pump for open/closed center	33	1516

Add Suffix "U" for flange (220 x 200) 9303C - Add \$40

Add Suffix "U" for flange (220 x 220) 9306C - Add \$40



9000 SERIES
 • 1 1/2" Inlet
 • 1 1/4" Outlet
 • Cast Iron
 • Oil-lubricated gear drive

PART	MAX GPM	MAX PSI	MAX RPM	HYPRO GEAR-DRIVEN PUMPS DESCRIPTION	lbs ea.	PRICE
9006C-O	117	80	540	1 3/8" female PTO hub w/ locking collar and mount clip	45	795
9008C-O	110	70	1000	1 3/8" female PTO hub w/ locking collar and mount clip	46	825
9016C-O	117	80	540	1" solid shaft	43	785
9018C-O	110	70	1000	1" solid shaft	43	815
9028C-O	110	70	1000	1 3/4" female PTO hub w/ locking collar and mount clip	49	957
3430-0334				Seal and o-ring repair kit	4oz	40
2120-0011				Seal only	4oz	34

Add Suffix "U" for flange (220 x 200) - Add \$40



PART	MAX GPM	MAX PSI	MAX RPM	HYPRO CAST IRON PEDESTAL-MOUNT PUMP DESCRIPTION	lbs ea.	PRICE
9203C	136	170	6000	5/8" solid shaft and Viton shaft seal	17	339
9203C-R	136	170	6000	5/8" solid shaft and Viton shaft seal - clockwise	17	347
3430-0332				Seal and o-ring repair kit ceramic	3oz	44



PART	MAX GPM	MAX PSI	MAX RPM	HYPRO CAST IRON BELT-DRIVEN PUMPS DESCRIPTION	lbs ea.	PRICE
9403C-540Q	140	104	600	1 3/8", 6-Spline quick coupler	44	805
9403C-540S	140	104	600	1" solid shaft	45	805
9403C-1000	140	104	1000	1 3/8" hollow shaft, 21 spline	42	805
9403C-1000L	140	104	1000	1 3/4" hollow shaft, 20 spline	42	836
9403C-1000S	140	104	1000	1" solid shaft	42	805

All Stainless Steel pumps listed have Life Guard™ silicon carbide