

MICRO-TRAK SPRAY CONTROLS



PART	DESCRIPTION	PRICE
MT-3405FII	Auto Spray Rate Controller Dual Display 5 Boom sections NH3 compatible	\$1204



MT-SM	Spraymate II Controller 3 Boom Sections Optional On/Off power switch	\$ 933
-------	--	--------

MICRO-TRAK[®]
SYSTEMS, INC.



MT-NH3II	Liquifier NH3 II Kit	\$ 563
MT01097	For MT-NH3 II	\$3196
MT01098	For Spray Mate II	\$3196
MT01133	For MT-3405F II	\$3196



Controllers priced less speed sensor - choose:

MT01530	Hall-effect Magnet wheel kit	\$145
MT01531	Magnetic Wheel kit	145
MT01529	Vansco Radar w/MT adaptor	496



ELECTRIC PUMP DRIVER		
MT14692	EPD replaces servo valve to control 12v pump up to a max of 20 amp for fertilizer applications.	310



MICRO-TRAK[®]
SYSTEMS, INC.
An Electronics Company



SERVO & FLOWMETERS

PART	DESCRIPTION	PRICE
MT14928	1" Servo	\$223
MT01515	Flow Master 270	459
MT01501	FM750GFN	282



CALC-AN-ACRE
MT10100 \$299

Accurate speed,
distance and area



astro II



ASTRO II GPS SPEED SENSOR

PART	DESCRIPTION	PRICE
MT01410	3-pin MT Base I & II M/P	\$279.90
MT01411	3-pin MT3000/5000 W/P	279.90
MT01412	2-pin (old Calc/FT /SOM)	279.90
MT01413	DJ 4-pin Amp	279.90
MT01414	4-pin DJ Packard	279.90
MT01415	3-pin Raven Conxall	279.90
MT01416	4-pin Magnavox/Phillips	279.90
MT01417	3-pin Tee Jet 844	279.90

TEEJET SPRAYER CONTROL SYSTEMS



TeeJet



844-E SPRAYER CONTROL

- Easily Accessible Programming Mode
- Color Coded Tip Selection Bar
- Individual Boom Controls
- Boost Mode will temporarily increase or decrease application rate, such as in patches of heavy weeds

TJ844EKIT \$1595

Replacement Parts

PART	DESCRIPTION	PRICE
35-02099	1" Regulating Ball Valve	\$199
35-02112	Flanged Regulating Valve	199
90-50230	801 Flowmeter 1" HB	413



854 SPRAYER CONTROL - CORE KIT

- Easily Accessible Programming Mode
- Color Coded Tip Selection Bar
- Individual Boom Controls
- Nine Field Memory Locations
- Tank Volume/Tank Fill
- Five Rate Presets

TJ854KIT \$1536

PART	DESCRIPTION	PRICE
45-05210	Direct 854 Console 26' -5 sect	\$356
45-20000	Junction box w/o power 21' -5	536
45-20065	Direct wiring, 26' -5	335